

635W **LB**
Series

Higher power generation better LCOE



n-type with very Lower LID



Better Temperature Coefficient



Better low irradiance response



12-year product warranty



30-year linear power output warranty

n-type Bifacial Double Glass High Efficiency Mono Module JAM72D42 LB

610-635

Comprehensive Certificates

- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems
- IEC 62941: 2019 Terrestrial photovoltaic (PV) modules - Quality system for PV module manufacturing






635W

610-635
JAM72D47

LB
Series



Remark: customized frame color and cable length available upon request

Cell	Mono-16BB
Weight	34.6kg
Dimensions	2465±2mm×1134±2mm×35±1mm
Cable Cross Section Size	4mm² (IEC), 12 AWC(UL)
No. of cells	144(6×24)
Junction Box	IP68, 3 diodes
Connector	QC 4.10-351
Cable Length (Including Connector)	1500mm(+)/1500mm(-)
Front Glass/Back Glass	2.0mm/2.0mm
Packaging Configuration	31pcs/Pallet, 496pcs/40HQ Container

ELECTRICAL PARAMETERS AT STC

TYPE	JAM72D42 -610/LB	JAM72D42 -615/LB	JAM72D42 -620/LB	JAM72D42 -625/LB	JAM72D42 -630/LB	JAM72D42 -635/LB
Rated Maximum Power(Pmax) [W]	610	615	620	625	630	635
Open Circuit Voltage(Voc) [V]	51.67	51.87	52.07	52.27	52.47	52.67
Maximum Power Voltage(Vmp) [V]	43.11	43.31	43.51	43.71	43.90	44.10
Short Circuit Current(Isc) [A]	15.01	15.06	15.11	15.16	15.21	15.26
Maximum Power Current(Imp) [A]	14.15	14.20	14.25	14.30	14.35	14.40
Module Efficiency [%]	21.8	22.0	22.2	22.4	22.5	22.7
Power Tolerance	0~+5W					
Temperature Coefficient of Isc(α_{Isc})	+0.046%/℃					
Temperature Coefficient of Voc(β_{Voc})	-0.260%/℃					
Temperature Coefficient of Pmax(γ_{Pmp})	-0.300%/℃					
STC	Irradiance 1000W/m², cell temperature 25℃, AM1.5G					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer. They only serve for comparison among different module types.

ELECTRICAL CHARACTERISTICS WITH 5% BACKSIDE POWER GAIN

TYPE	JAM72D42 -610/LB	JAM72D42 -615/LB	JAM72D42 -620/LB	JAM72D42 -625/LB	JAM72D42 -630/LB	JAM72D42 -635/LB
Rated Max Power(Pmax) [W]	641	646	651	656	662	667
Open Circuit Voltage(Voc) [V]	51.67	51.87	52.07	52.27	52.47	52.67
Max Power Voltage(Vmp) [V]	43.11	43.31	43.51	43.71	43.90	44.10
Short Circuit Current(Isc) [A]	15.76	15.81	15.87	15.92	15.97	16.02
Max Power Current(Imp) [A]	14.86	14.91	14.96	15.02	15.07	15.12
Irradiation Ratio (rear/front)	5%					


*For Nextracker installations, maximum static load please take compatibility approve letter between JA Solar and Nextracker for reference.

$$^{**}\text{Bifaciality} = P_{\text{max, rear}} / \text{Rated } P_{\text{max, front}}$$

CHARACTERISTICS

 Superior Warranty

1% 1st-year Degradation
0.4% Annual Degradation Over 30 years





- n-type Bifacial Double Glass Module Linear Performance Warranty
- Standard Module Linear Performance Warranty

OPERATING CONDITIONS

Maximum System Voltage	1500V DC
Operating Temperature	-40 °C ~+85 °C
Maximum Series Fuse Rating	30A
Maximum Static Load,Front*	5400Pa(112 lb/ft²)
Maximum Static Load,Back*	2400Pa(50 lb/ft²)
NOCT	45±2 °C
Bifaciality**	80%±10%
Fire Performance	UL Type 29

Current-Voltage Curve **JAM72D42-620/LB**

Power-Voltage Curve **JAM72D42-620/LB**

Current-Voltage Curve **JAM72D42-620/LB**

